SAFETY DATA SHEET



Date of issue/Date of revision 28 September 2015

Version 2

Section 1. Identification

Product name : Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Product code : 01049

Other means of : This MSDS covers all PPG CVD coated glass including, but not limited to: IntelliGlaze, identification : AquaGlaze coated glass substrates, Sungate® 500, Sungate® 600, Sunclean®,

Solarcool® coated glass substrates, Vistacool™ coated glass substrates, Solar TCO,

Solarphire™ TCO.

Product type : Article

Relevant identified uses of the substance or mixture and uses advised against

Product use : Glass.

Use of the substance/

mixture

: Coating. Paints. Painting-related materials.

Uses advised against : Not applicable.

Supplier : PPG Industries, Inc.

One PPG Place Pittsburgh, PA 15272

Emergency telephone

number

: (412) 434-4515 (U.S.)

Technical Phone Number : 1-412-820-8500 (Flat Glass/Trade)

Section 2. Hazards identification

OSHA/HCS status : This product is considered an article. The end use is dependent upon the manufactured

shape and design, and this article will not pose an exposure hazard under normal

conditions.

Sanding and grinding this article can generate nuisance dust particles. Sanding and grinding dusts May be irritating to eyes and respiratory system.

Classification of the : Not classified.

substance or mixture

GHS label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

United States Page: 1/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 2. Hazards identification

Disposal Supplemental label

elements

: Not applicable.: None known.

Hazards not otherwise

classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

Product name

: Article

Other means of identification

: Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

: This MSDS covers all PPG CVD coated glass including, but not limited to: IntelliGlaze, AquaGlaze coated glass substrates, Sungate® 500, Sungate® 600, Sunclean®, Solarcool® coated glass substrates, Vistacool™ coated glass substrates, Solar TCO,

Solarphire[™] TCO.

Ingredient name	%	CAS number
glass, oxide, chemicals	60 - 100	65997-17-3

composition consisting primarily of oxides of silicon with lesser quantities of other selected oxides common to soda-lime glasses, fused into an amorphous vitreous state.

Note: Glass sheets are typically stacked for shipment and may be separated with less than 1 weight percent of powdered interleaving material consisting of organic acid coated polymeric beads. Exposure to these polymeric beads is not expected to be a concern. Glass surface may also be coated with a solution of a mild organic acid. The dried residue on the glass is less than 1% by weight. In handling the glass, exposure to the mild organic acid is not expected to be a concern. The only potential impact may be on the pH of the waste water effluent after glass washing to remove the residue and interleaving.

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact : (Sanding and grinding dusts) In case of contact with eyes, rinse immediately with plenty

of water and seek medical advice. Check for and remove any contact lenses.

Inhalation: None known.Skin contact: None known.

Ingestion : Not a likely route of exposure.

Most important symptoms/effects, acute and delayed

United States Page: 2/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 4. First aid measures

Potential acute health effects

Eye contact (Sanding and grinding dusts) No significant irritation expected other than possible

mechanical irritation.

Inhalation : (Sanding and grinding dusts) May cause slight transient irritation.

Skin contact (Sanding and grinding dusts) No significant irritation expected other than possible

mechanical irritation.

Ingestion : Not a likely route of exposure.

Over-exposure signs/symptoms

Eye contact : No specific data. Inhalation : No specific data. **Skin contact** : No specific data. Ingestion : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. **Specific treatments** : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

No specific data.

Specific hazards arising

from the chemical

Hazardous thermal

decomposition products

: No specific fire or explosion hazard.

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Special protective equipment for fire-fighters

: No special protection is required.

United States Page: 3/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

: No special protection is required.

For emergency responders : No special protection is required.

Environmental precautions

: No specific hazard.

Methods and materials for containment and cleaning up

Small spill

: Vacuum or sweep up material and place in a designated, labeled waste container.

Large spill

: Vacuum or sweep up material and place in a designated, labeled waste container.

Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Take care with items that are sharp or heavy. Any glass can have sharp edges, particularly at a cut or fractured edge. Normal strength glass, also known as annealed or float glass, is known to fracture into large sections with sharp edges. Chemically strengthened or chemically tempered glass and thermally heat-strengthened glass will tend to fracture much the same as normal strength annealed glass, and are not considered safety glazing products. Thermally tempered glass (commonly known as fully tempered glass or safety glazing) will fracture into many smaller pieces still capable of cutting skin, but typically not as severely as would larger fragments from normal strength annealed glass. These safety concerns should be addressed with proper personal protective equipment to protect oneself against any sharp edges, including those formed by accidental glass fracture during handling. Sanding (a.k.a. seaming or edging) any sharp glass edges to produce rounded edges also reduces the hazards with being cut by sharp edges.

Advice on general occupational hygiene : Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in a dry place away from excessive moisture and exhaust fumes from fork trucks or other such equipment. Support glass in cases on both sides when stored vertically. Glass packs and open cases should be stored at a 5° lean angle to prevent glass from falling forward.

> **United States** Page: 4/10

Date of issue 28 September 2015 Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
Sanding and grinding dusts	OSHA PEL (United States). TWA: 15 mg/m³ TWA: 5 mg/m³ Form: Respirable TWA: 15 mg/m³ Form: Total dust ACGIH TLV (United States). TWA: 5 mg/m³ Form: Inhalable TWA: 3 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total dust

Key to abbreviations

S Α = Acceptable Maximum Peak = Potential skin absorption ACGIH = American Conference of Governmental Industrial Hygienists. SR = Respiratory sensitization = Ceilina Limit SS = Skin sensitization С F STEL = Short term Exposure limit values **IPEL** = Internal Permissible Exposure Limit TD = Total dust = Occupational Safety and Health Administration. **OSHA** TI V = Threshold Limit Value R = Respirable TWA = Time Weighted Average

Consult local authorities for acceptable exposure limits.

Recommended monitoring: Not applicable

procedures

= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances

Appropriate engineering controls

Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Not applicable.

Individual protection measures

Hygiene measures

: Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection **Skin protection**

Safety glasses with side shields.

Hand protection : Rubber dipped anti-lacerative gloves are recommended.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: (Sanding and grinding dusts) If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

> **United States** Page: 5/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 9. Physical and chemical properties

Appearance

Physical state : Solid. Color : tinted Odor : Odorless. : Not applicable. **Odor threshold** pН : Not applicable.

Melting point : 1300 °F (704°C) (softening point)

Boiling point : Not applicable.

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

: Not applicable **Auto-ignition temperature Decomposition temperature** : Not applicable. Flammability (solid, gas) : Not applicable. Lower and upper explosive : Not applicable.

(flammable) limits

Evaporation rate : Not applicable. Vapor pressure : Not applicable. Vapor density : Not applicable.

Relative density 2.45 **2**0.45 Density (lbs/gal)

: Not applicable. **Solubility** Partition coefficient: n-: Not applicable.

octanol/water

Viscosity : Not applicable. **Volatility** : 0% (v/v), 0% (w/w)

% Solid. (w/w)

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Not applicable.

Conditions to avoid : No specific data.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

United States Page: 6/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Conclusion/Summary

: No known significant effects or critical hazards.

Irritation/Corrosion

Conclusion/Summary

Skin
 Eyes
 No known significant effects or critical hazards.
 Respiratory
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Sensitization

Conclusion/Summary

Skin : No known significant effects or critical hazards.Respiratory : No known significant effects or critical hazards.

Mutagenicity

Conclusion/Summary :

: No known significant effects or critical hazards.

Carcinogenicity

Conclusion/Summary: No known significant effects or critical hazards.

Reproductive toxicity

Conclusion/Summary: No known significant effects or critical hazards.

Teratogenicity

Conclusion/Summary: No known significant effects or critical hazards.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Target organs : Contains material which may cause damage to the following organs: upper respiratory

tract, skin, eyes. (Sanding and grinding dusts)

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact : (Sanding and grinding dusts) No significant irritation expected other than possible

mechanical irritation.

Inhalation : (Sanding and grinding dusts) May cause slight transient irritation.

Skin contact : (Sanding and grinding dusts) No significant irritation expected other than possible

mechanical irritation.

Ingestion : Not a likely route of exposure.

Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

United States Page: 7/10

Date of issue 28 September 2015 Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 11. Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary: Not available.

Short term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects : No known significant effects or critical hazards.

Long term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Not available.

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

United States Page: 8/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	None.	-	-
Packing group	-	-	-
Environmental hazards Marine pollutant substances	No. Not applicable.	No. Not applicable.	No. Not applicable.

Additional information

DOT : None identified.IMDG : None identified.IATA : None identified.

Special precautions for user: Not applicable.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b): All components are listed or exempted.

U.S. Federal regulations

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Not applicable.

Composition/information on ingredients

No products were found.

United States Page: 9/10

Date of issue 28 September 2015Version 2

Product name Chemical Vapor Deposition (CVD) and Spray Pyrolysis Coated Float Glass

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 0 Flammability: 0 Physical hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 0 Flammability: 0 Instability: 0

Other information : The PPG logo is a registered trademark of PPG Industries Ohio, Inc.

Date of previous issue : 12/16/2014

Organization that prepared : EHS

the MSDS

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 10/10