



SXSW Office Tower



Pegasus Park



SAFE Credit Union Performing Arts Center

Solarban® 90 Solar Control Low-e Glass

Solar Control Without Sacrifice

Introduced as the world's first quad-silver glass in 2015, Solarban® 90 glass delivers outstanding solar control with a true neutral-reflective appearance.

	1-Inch IGU on Clear (2)		Substrate Options		
	SHGC	VLT%	Clear	Low-Iron	Tinted
	0.23	51	✓	✓	✓

Aesthetic: Neutral

Reflectivity: Low

Availability				
Titan™ Glass Sizes	BirdSmart® Glass	Annealed	Heat Treatable	Vitro Certified® Network
✓	✓		✓	✓

Compatibility			
Laminated	Bent	Heat Soaked Testing	Used With Sungate ThermL™ Glass
✓	✓	✓	✓

Insulating Glass Unit Performance Comparisons | 1-inch (25 mm) units with 1/2-inch (13 mm) airspace and two 1/4-inch (6 mm) lites

Outdoor Lite: Coating if Any (Surface) Glass	Glass Type + Indoor Lite: Coating if Any (Surface) Glass	Visible Light Transmittance (VLT) %	Visible Light Reflectance		(BTU/hr²ft²°F) NFRC U-Value		Solar Heat Gain Coefficient (SHGC)	Color Rendering Index (CRI)
			Exterior %	Interior %	Winter Nighttime	Winter Argon		

Solarban® 90 Solar Control Low-e Glass


Solarban® 90 (2) Clear + Clear	51	12	19	0.29	0.24	0.23	92
Solarban® 90 (2) Acuity® + Acuity®	53	12	19	0.29	0.24	0.23	94
Solarban® 90 (2) Starphire® + Starphire®	54	13	20	0.29	0.24	0.23	95
Solarban® 90 (2) Solexia® + Clear	44	10	19	0.29	0.24	0.22	86
Solarban® 90 (2) Azuria® + Clear	39	9	19	0.29	0.24	0.21	75
Solarban® 90 (2) Optiblue® + Clear	37	8	19	0.29	0.24	0.20	88
Solarban® 90 (2) Solarblue® + Clear	32	8	18	0.29	0.24	0.19	81
Solarban® 90 (2) Solarbronze® + Clear	31	7	18	0.29	0.24	0.18	94
Solarban® 90 (2) Optigray® + Clear	36	8	19	0.29	0.24	0.20	90
Solarban® 90 (2) Solargray® + Clear	26	6	18	0.29	0.24	0.17	90
Atlantica® + Solarban® 90 (3) Clear	39	13	12	0.29	0.24	0.26	82
Solarban® 90 (2) Pacifica® + Clear	24	6	18	0.29	0.24	0.17	69
Graylite® II + Solarban® 90 (3) Clear	5	4	11	0.29	0.24	0.11	82

All performance data calculated using LBNL Window 7.8 software and represents center of glass performance data. For detailed information on the methodologies used to calculate the aesthetic and performance values in this table, please visit vitroglazings.com or request our Architectural Glass Catalog.

Sustainability

All Vitro Architectural Glass Products meet US GSA Low-Embodied Carbon standards.

Vitro is the first U.S. glass manufacturer to have its entire collection earn **Cradle to Cradle Certified®** recognition and first North American glass manufacturer to publish **Environmental Product Declarations (EPDs)** for Flat and Processed Glass Products.



For more information visit vitroglazings.com, or call 1-855-VTRO-GLS (887-6457).

To order samples, visit samples.vitroglazings.com

Projects

Pegasus Park | Dallas, Texas | Solarban® 90 Acuity® Glass | Architect: GFF | Glass Fabricator: Tristar Glass Inc. Glazing Contractor: Sunbelt Waterproofing | Photographer: Tom Kessler

SAFE Credit Union Performing Arts Center | Sacramento, California | Solarban® 90 Acuity® Glass | Architect: DLR Group Glass Fabricator: Glassfab Tempering Services | Glazing Contractor: Bagatelos Architectural Glass Systems | Photographer: Tom Kessler

SXSW Office Tower | Austin, Texas | Solarban® 90 Glass | Architect: Pei Cobb Freed & Partners, Gensler Glass Fabricator: OldCastle BuildingEnvelope® | Photographer: Tom Kessler



Solarban® 90 Starphire® Glass