Less green. For less green.



NC A&T Engineering Research and Innovation Complex (ERIC) | Greensboro, North Carolina | Solarban® 90 Acuity® Glass Architect: EYP | Vitro Certified® Fabricator: Press Glass | Glazing Contractor: Charlotte Glass | Photographer: Jim Sink Photography





Find affordable clarity in the *Solarban® Acuity®* low-e glass series.

The right glass can be the centerpiece of your design. Combining Vitro's new Acuity[®] low-iron glass – which is 60 percent less green than ordinary clear glass – with any *Solarban*[®] low-e coating, can provide the truly clear look you want with the outstanding energy and code performance you need.

An Engineered System

Leveraging 30 years of *Starphire Ultra-Clear*[®] glass manufacturing experience, *Acuity*[®] low-iron glass is specifically engineered for vision glazings, both as a substrate for *Solarban*[®] coatings and for all lites in an insulating glass unit (IGU) or laminated configuration. This combination provides excellent transparency and clarity at an affordable upcharge from coated clear glass.

Where to Use Solarban® Acuity® Glass

Solarban[®] Acuity[®] glass is optimized for vision glazings or any exterior application where excellent clarity and low-e performance are needed.

Consider Solarban® Acuity® glass for the following applications:

- Office buildings and institutions
- Hotels
- Schools
- Luxury condos & mixed-use
- Entrances & retail storefronts

Solarban® Acuity[®] glass also is ideal for distinctive exterior applications, such as atriums, skylights and spandrel glass. For configurations that require exposed edges, such as interior applications, Vitro recommends *Starphire Ultra-Clear*[®] low-iron glass for its signature azure blue edge and sparkling clarity.



Parkland Health and Hospital System Moody Outpatient Center Dallas, Texas | Solarban® 90 Acuity® Glass | Architect: HKS Vitro Certified® Fabricator: Hartung Glass Industries (formerly NWI) Glazing Contractor: IWR North America Photographer: Tom Harris Architectural Photography



SAFE Credit Union Performing Arts Center | Sacramento, California Solarban® 90 Acuity® Glass | Architect: DLR Group Vitro Certified® Fabricator: Glassfab Tempering Services Glazing Contractor: Bagatelos | Photographer: Tom Kessler

Optimizing Cost, Clarity & Performance

Cost Considerations

Vitro market research indicates the installed cost of a standard glass and metal curtainwall averages \$90 per square foot nationally. Upgrading a low-e coated clear IGU to a *Solarban® Acuity®* glass unit typically will increase the total installed curtainwall cost by only \$1 to \$2 per square foot.

This optimization of cost, clarity and performance allows you to make *Solarban® Acuity®* glass the centerpiece of your façade design.

Design Considerations

Acuity[®] low-iron glass is 60 percent less green than standard "clear" glass. Solarban[®] Acuity[®] glass achieves excellent clarity and 1 to 3 percent higher visible light transmittance (VLT) than coated clear glass.

For the ultimate in transparent low-iron glass, *Starphire*[®] glass is 87 percent less green and also can be coated with *Solarban*[®] low-e coatings.



Fabrication & Availability

Available in 6, 8 and 10 millimeter thicknesses, *Solarban® Acuity®* glasses are stocked at all Vitro facilities for immediate shipment with the same lead time as all *Solarban®* glass products. *Acuity®* glass also can be cut, drilled, heat-treated, laminated and bent, just like any low-iron glass or glass substrate.

All *Solarban®* solar control low-e glasses are available through the *Vitro Certified®* Network.

For more information about *Solarban® Acuity®* low-iron glass and other architectural glasses by Vitro Glass, visit vitroglazings.com/acuity, or call 1-855-VTRO-GLS (887-6457).



\$1-2 per square foot

COST INCREASE* In total installed glass and metal curtainwall costs (compared to a low-e coated

APPEARANC

60% Less Green

than Clear Glass*

omparison of unco substrates

Supporting Sustainable Design

Vitro Architectural Glass provides abundant opportunities for architects and building owners to realize their sustainability objectives.

Energy Use & Operating Cost Reduction: High-performance glasses by Vitro are engineered to facilitate downsized mechanical equipment costs, leading to reduced long-term energy costs. For glass comparison and configuration tools, visit **tools.vitroglazings.com**. **Sustainability Documentation:** Vitro Architectural Glass is the first U.S. float glass manufacturer to have its entire selection of products recognized by the *Cradle to Cradle Certified®* program, and the first in North America to publish third-party verified EPDs for its Flat Glass and Processed Glass products.

For additional credit opportunities and supporting documentation, visit **vitroglazings.com/LEED**

LEED [®] Credit Opportunities									
Possible Points	LEED Credit	Solarban® Acuity® Feature	Path/Option Satisfied						
18	Energy & Atmosphere (EA) Optimize Energy Performance	Excellent SHGC, U-value and Tvis performance	Whole Building Energy Simulation (Option 1) or Prescriptive Compliance: ASHRAE Advanced Energy Design Guide (Option 2)						
5	Innovation (IN) Innovation in Design	Exceeds minimum performance mandated by local energy codes	Innovation (Option 1), Pilot (Option 2) and Exemplary Performance (Option 3)						
3	Indoor Environmental Quality (EQ) Daylight	Exhibits high light transmission	Simulation: Spatial Daylight Autonomy and Annual Sunlight Exposure (Option 1), Simulation: Illuminance Calculations (Option 2) or Measurement (Option 3)						

Performance Data for Solarban® Acuity® Low-E Low-Iron Glass

Insulating Glass Unit (IGU) Performance Comparisons 1-inch (25 mm) units with 1/2-inch (13 mm) airspace and two 1/4-inch (6 mm) lites										
Glass Type	Visible Light Transmittance (VLT) %	Visible Light Reflectance		(Btu/hr∙ft²•°F) NFRC U-Value		Solar Heat Gain	Color Rendering			
Coating if Any + Coating if Any (Surface) Glass (Surface) Glass		Exterior %	Interior %	Winter Nighttime	Winter Argon	Coefficient (SHGC)	Index (CRI)			
Coated										
SOLARBAN® 60 Solar Control Low-e Glass										
SOLARBAN 60 (2) ACUITY + ACUITY	73%	11%	12%	0.29	0.24	0.41	97			
SOLARBAN® R67 Solar Control Low-e Glass										
SOLARBAN R67 (2) ACUITY + ACUITY	56%	19%	16%	0.29	0.24	0.30	94			
SOLARBAN® 72 Solar Control Low-e Glass										
SOLARBAN 72 (2) ACUITY + ACUITY	67%	13%	14%	0.28	0.24	0.28	94			
SOLARBAN [®] 90 Solar Control Low-e Glass										
SOLARBAN 90 (2) ACUITY + ACUITY	53%	12%	19%	0.29	0.24	0.23	94			
SOLARBAN® R77 Neutral-Reflective Low-e Glass										
SOLARBAN R77 (2) ACUITY + ACUITY	49%	26%	16%	0.29	0.24	0.25	95			
SOLARBAN® R100 Neutral-Reflective Low-e Glass										
SOLARBAN R100 (2) ACUITY + ACUITY	43%	33%	13%	0.29	0.25	0.23	92			

All performance data calculated using LBNL Window 7.3 software and represents center of glass performance data. For detailed information on the methodologies used to calculate the aesthetic and performance values in this table, please visit vitroglazings.com or request our Architectural Glass Catalog.

Additional Resources

To obtain samples of any Vitro Glass product, call 1-855-VTRO-GLS (877-6457) or visit **samples.vitroglazings.com**. For videos, design insights and technical education, visit the Vitro Glass Education Center at **glassed.vitroglazings.com**. For glass comparison and configuration tools, visit **tools.vitroglazings.com**.

©2023 Vitro Architectural Glass. All rights reserved. Acuity®, Solarban®, the Solarban® Acuity® logo, Starphire®, Starphire Ultra-Clear®, Vitro Certified®, Vitro® and the Vitro® logo are registered trademarks owned by Vitro. Cradle to Cradle Certified® is a registered trademark licensed by the Cradle to Cradle Products Innovation Institute. LEED® — an acronym for Leadership in Energy and Environmental Design® — is a registered trademark of the U.S. Green Building Council®. Printed in the USA. 7210 (11/2023)



